

# WOODS FINISH MOWERS



Discover the premium cut quality that makes  
Woods the undisputed leader in finish mowers

**WOODS**



### Table of Contents

<b>Rear Discharge Mowers</b> .....	<b>4</b>
RDC54	
RD60	
RD72	
PRD6000	
PRD7200	
PRD8400	
RD990X	
<b>Specifications Chart</b> .....	<b>6</b>
<b>Turf Batwing® Rear Discharge Mowers</b> .....	<b>8</b>
<b>Estate</b> .....	<b>9</b>
TBW150C	
<b>Commercial</b> .....	<b>10</b>
TBW144	
TBW180	
TBW204	
<b>Turf Batwing Specifications Chart</b> .....	<b>11</b>

**Woods**  
GENUINE PARTS



Since 1946, we've been manufacturing in Oregon, Illinois, and supporting the growth of American jobs.

**Woods**  
GENUINE PARTS

Maintain the quality and performance of your Woods equipment with Woods genuine replacement parts, paint, and lubricants. Available from your authorized Woods dealer.

#### Find a Woods Dealer

Woods equipment is distributed through a network of authorized dealers. To find your nearest store visit us at [woodsequipment.com](http://woodsequipment.com) or call 800-319-6637.

## Designed for Speed

**Woods finish mowers help you maintain a beautiful lawn in less time. You'll look forward to using your equipment with features that focus on your drive to get more done.**

- Unique to the industry, our rounded front, tapered-side rear discharge deck allows you to mow with better maneuverability — reducing your trim time and increasing your productivity
- Spring-loaded idler arms automatically maintain the correct tension on our strong custom-made belts, providing optimum run time

## Precision and Quality

**For those who demand a professionally groomed lawn, Woods high-performance finish mowers ensure a clean, crisp, manicured appearance every time.**

- The combination of a deep deck, baffling and unique rear discharge design ensures exceptional material distribution and gives you the premium results that make the Woods name synonymous with “cut quality”
- Manufactured exclusively to Woods’ superior standards, heat-treated, alloy steel blades provide maximum performance and precision cutting applications, such as large lawns, parks and sporting fields
- Cast-iron belt sheaves with taper lock bushings and tapered roller bearings in the spindles offer exceptional strength and performance; standard on RD990X, PRD and commercial TBW models



RD990X



# WOODS



## Tubular Caster Arms

And heavy, 4.5-inch-tall deck rail supports increased strength and product life

## RDC54

shown with optional chain shielding\*

## Deep Deck

4.6-inch deck depth, along with baffling and rear discharge design, ensure exceptional material distribution and a higher quality of cut

## Tractor PTO Range: 15 – 35 hp

### Model

<b>RDC54</b>	54-inch cutting width
<b>RD60</b>	60-inch cutting width
<b>RD72</b>	72-inch cutting width

- Three-point hitch: Limited Cat 1 and Cat 1
- Cutting width covers tractor tire tracks and reduces mowing time
- Rounded front corners and tapered sides improve maneuverability and grass discharge while box-style construction offers superior deck strength
- Blade tip speeds of: 16,200 fpm, 18,030 fpm, and 18,000 fpm

## Rear Discharge Mowers

Every rear-mount model in the Woods line-up offers the best features within our full line of finish mowers.

- Designed for 15–75 horsepower tractors
- High performance gearboxes require less maintenance
- Industrial quality, reinforced blade spindle is designed for years of service
- Available in a range of cutting widths from 4.5 to 7.5 feet
- Floating top link helps prevent scalping
- ASABE quick-hitch compatibility ensures faster and easier hook-ups (not available on RDC54)
- Floating lower hitch points allow the mower to follow uneven terrain



## Tractor PTO Range: 15 – 40 hp

### Models

<b>PRD6000</b>	60-inch cutting width
<b>PRD7200</b>	72-inch cutting width
<b>PRD8400</b>	84-inch cutting width

- Three-point hitch: Cat 1
- Ideal for mowing lawns, sports fields, and parks
- Features a strong, eight gauge steel deck and a powerful 60 hp gearbox
- Kevlar® belt with clutching cover protects parts and increases lifespan
- Anti-shimmy caster wheel springs reduce shock loads — tubular caster wheel arms add strength



**PRD7200**  
shown with optional  
chain shielding\*



**RD990X**



### Quick Attach Blades

Exclusive quick attach blades provide ease of service — blades can be changed quickly with only 3/4" wrench.

## Tractor PTO Range: 45 – 75 hp

### Model

<b>RD990X</b>	90-inch cutting width
---------------	-----------------------

**The Woods RD990X rear discharge finish mower is tough yet versatile enough to move from rough, weedy farmland to commercial lawns and landscapes.**

- Three-point hitch: Cat 1 and 2
- Blade tip speed: 17,000 fpm
- Free swinging blades
- Deep deck and swinging blades are ideal for rough grass
- Takes down grass and light weeds, and leaves a high grade finish cut behind
- Chain shielding standard

**\*NOTE:** All RD-Series finish mower models pass all applicable safety standards for thrown object and blade contact without chain shielding. However, if these units will be used in areas where the possibility of thrown objects could be hazardous to persons or property, it is strongly recommended that optional chain shielding be used for extra protection.

Specifications	RDC54	RD60	RD72
Tractor PTO HP	15–25 hp	15–35 hp	20–35 hp
Hitch/Quick-Hitch Compatible	Limited Cat 1 / no	Cat 1 / yes	
Cutting Width	54"	60"	72"
Weight	401 lbs	503 lbs	603 lbs
Cutting Height Range	1"–4.5"		
Overall Width	55"	61"	73"
Deck Material Thickness	10 gauge	8 gauge	
Side Skirt	10 gauge x 4.6" deep	8 gauge x 4.6" deep	
Gearbox HP Rating	25 hp	35 hp	
Blade Tip Speed	16,200 fpm	18,030 fpm	18,000 fpm
Blade Overlap	1"	1.5"	
Blade Spindles/Bearings	3 cast iron housings / greasable ball bearings		
Blade Sheave	steel		
Blade Crossbar	no		
Caster Wheels	3.25" x 10" solid rubber or 3.5" x 4" x 10" pneumatic		
Tractor PTO Speed	540 rpm		
Driveline Size	Cat 3		
Belt	B-section Kevlar®		
Belt Adjustment			
Front Center Roller or Front Anti-Scalp Roller			
Cutting Area Shielding	optional chain shielding		
Mulching Kit	no		
Mower Warranty	1 year residential, 90-day commercial		
Gearbox Warranty	3-year homeowner, 1 year commercial		
Spindle Warranty	no		

PRD6000	PRD7200	PRD8400	RD990X
15–40 hp	20–40 hp	25–40 hp	45–75 hp
Cat 1 / yes			Cat 1 and 2 / yes
60"	72"	84"	90"
653 lbs	719 lbs	830 lbs	1,333 lbs
1"–5.5"		1"–4.25"	1.5"–7"
62"	74"	86"	97"
8 gauge			7 gauge
8 gauge x 5.375" with .5625" diameter skid rod bumper			.31" thick x 8.50" with skid shoes
60 hp, 6 year limited warranty			75 hp
18,100 fpm	18,000 fpm	17,900 fpm	17,000 fpm
1.5"		2"	2"
3 cast iron housings / greasable tapered roller bearings			
cast-iron with taper-lock bushing			
yes			yes, free swinging blades
4" x 10" solid or 4" x 10" pneumatic			5" x 13" solid or 5" x 13" pneumatic
540 rpm			
Cat 3			Cat 4
B-section Kevlar® with clutching cover			Powerband with double B-section Kevlar®
spring-loaded idler			
optional			
optional chain shielding			standard chain shielding
optional			–
1 year			1 year
6 years			6 years
3 years			3 years



# WOODS

## Turf Batwing® Mowers

Our flexible wing finish mowers feature Woods' proven cutting deck in a three-gang configuration mounted to a heavy-duty trailer.

- Carrier bearing on the CV (constant velocity) input driveline provides support, making it easier to attach to the tractor and allowing tighter turns (not available on TBW150C)
- Superior cutting capabilities are combined with contoured wing decks to let you quickly cut large, uneven areas of turf without sacrificing cut quality
- Rounded front, tapered rear deck design allows mowing close to objects without damage
- Round skid rod glides deck bottom over roots and uneven turf — adding strength to the deck skirt
- Standard six-year gearbox limited warranty and three-year spindle warranty (not available on TBW150C)
- Floating hitch design flexes to allow the mower to follow the terrain with less stress and wear on the tractor drawbar. Adjustable to allow better fit on multiple tractor drawbar heights. Standard on the TBW144, TBW180 and TBW204

TBW180



## Transport Latching System

The transport latching system automatically engages when the decks are raised into transport position. Simply pull the release rope or engage the optional hydraulic latch release to lower the decks into the operating position with minimum effort.





### Folds for Storage

With a folded transport width of only 93 inches the TBW150C can fit into a standard 8-foot garage door

## Tractor PTO Range: 25 - 60 hp

### Estate Model

This 12.5-foot mower provides a beautifully finished cut making short work of large lawns. Based on testimonials, the TBW150C could reduce two days of mowing into as little as four-and-a-half hours.

#### Model

**TBW150C** 12.5-foot cutting width

- Blade tip speed: 16,200 fpm
- Decks are designed with “box” construction which adds structural strength
- Three decks mounted to heavy-duty trailer for triple cut capacity; mow up to seven acres per hour at five miles per hour
- Anti-scalp rollers standard



**TBW150C**  
shown with optional  
chain shielding\*

**\*NOTE:** The TBW150C mower passes all applicable safety standards for thrown objects and blade contact. However, if the unit will be used in areas where the possibility of thrown objects could be hazardous to persons or property, it is strongly recommended that optional chain shielding be used for extra protection.

# WOODS

## Turf Batwing® Mowers

**Tractor PTO Range:**  
**30 – 80 hp**

### Commercial Models

**Woods commercial Turf Batwing® finish mowers are designed for outstanding cut quality and built for a long, durable life.**

#### Models

<b>TBW144</b>	12-foot cutting width
<b>TBW180</b>	15-foot cutting width
<b>TBW204</b>	17-foot cutting width

- Blade tip speeds: 18,000 fpm
- Optional mulching kit available on the TBW180 and TBW204; highway light kit and anti-scalp roller options available on all three models
- Ten large caster wheels provide even cut on rough ground

#### **Durable Sheaves, Bushings and Spindles**

Cast-iron belt sheaves with taper lock bushings and tapered roller bearings in cast-iron spindles offer exceptional strength and performance. Spindles carry a 3-year warranty.

#### **Automatic Idler Corrects Belt Tension**

Spring loaded idler automatically maintains the correct belt tension for significantly increased belt life.

#### **Hydraulic Latch Release**

The optional hydraulic cylinder releases the transport lock to lower the decks into mowing position.



**TBW180**



Specifications	TBW150C	TBW144	TBW180	TBW204
Tractor PTO HP	25–60 hp	30–80 hp	35–80 hp	40–80 hp
Hitch Adjustment	floating clevis, multi-position			
Cutting Width	12.5 ft	12 ft	15 ft	17 ft
Cutting Height Range	1" to 4.5"	1" to 5"		
Wing Deck Cutting Width	54"	48.5"	60"	72"
Deck Overlap	6"	6.5"	6"	6"
Overall Width	151"	146"	182"	206"
Transport Width	93"	96"	100"	114"
Maximum Overall Length	135"	173"	183"	
Transport Length	126"	158"	161"	
Splitter Gearbox HP	100 hp			
Blade Tip Speed	16,200 fpm	18,000 fpm		
Drive Type	gearbox over v-belt			
Input Driveline	Cat 3 (constant velocity)	Cat 4 (constant velocity)		
Wing Drivelines	Cat 3			
Transport Tires	(2) 20" x 8"	(2) 20.5" x 8"-10"		
Caster Wheel Bearings	power metal bushing	tapered roller bearings		
Caster Wheels	(10) 4" x 10" solid	(10) 15" x 6-6" pneumatic	(10) 18" x 9.5-8" pneumatic	
Deck Thickness	10 gauge steel plate	8 gauge		
Wing Deck Lift Cylinders	3" x 10" single acting	3.5" x 10" single acting		
Center Deck Lift Cylinders	3" x 8" single acting			
Trailer Frame Construction	.25" wall tubing			
Blade Spindles Bearings	greasable ball bearings	greasable tapered roller		
Blade Dimensions	(9) .25" x 2.5"	(7) .25" x 2.5"	(9) .25" x 2.5"	
Blade Spindles	(9) cast iron	(7) cast iron	(9) cast iron	
Cutting Height Adjustment	spacer on caster			
Belts	B-section, Kevlar®			
Belt Adjustment	spring-loaded idler			
Cutting Area Shielding	optional chain shielding	standard chain shielding		
	Estate	Commercial		





**Got ideas?**  
Join our customer panel at [woodsequipment.com/power](http://woodsequipment.com/power).  
**You have the power...**

**WOODS®** | A Blount International Brand  
2606 South Illinois Route 2, Oregon, Illinois 61061 tel 800-319-6637 [woodsequipment.com](http://woodsequipment.com)



Warning! Some images may show safety shields removed to provide a better view. Equipment should never be operated with any safety shield removed. Some machines in this brochure may be shown with optional equipment. Always operate machines in accordance with supplied operator's manuals. ©2018 Woods Equipment Company. All rights reserved. WOODS, and the Woods logo are trademarks of Woods Equipment Company. All other trademarks, trade names, or service marks not owned by Woods Equipment Company that appear in this brochure are the property of their respective companies or mark holders. Specifications subject to change without notice.