

Woods BW15.72QRW Extreme Heavy-Duty 15' Batwing™ Slasher

The Woods BW15.72QRW Batwing™ slasher is an Extreme Heavy-Duty Flex Wing slasher built in America with exclusive features that give you an advantage in any field.

Specification	BW15.72QRW– Extreme Heavy Duty
Tractor PTO HP	90-300hp
Tractor PTO (rpm)	1,000rpm
Adjustable Cutting Height (mm)	50mm – 380mm
Cutting Capacity (mm)	115mm
Gearbox Rating (hp)	275hp splitter/225hp spindle
Blade Speed (fpm)	1,000rpm: 15,708 (wing) 16,132 (centre)
Blade Size (mm)	101.6mm x 12.7mm
Blade Overlap (mm)	152mm
Weight (kg)	2,556kg
Transport Width (m) – truck	2.43m (with hydraulics down)
Transport Width (m) – towing	3m (at full height)
Hydraulic Flex Wing	90° up, 22° down
Side Skirt	6.5mm thick, 330mm deep
Stump Jumper	Round
Wheels	6 x 25.5 severe duty ag foam filled aircraft tyres
Driveline Rating	CAT 6 CV main, CAT 5 wing
Output Shaft Diameter (in)	3 inches
Gearbox Warranty (yrs)	10 years
Structure Warranty (yrs)	2 years

Exclusive Features

- **Unmatched Gearbox Protection: 10-year warranty** including, parts, labour and seals. Gearbox also features Woods Exclusive **Cool-Flow™** Lubrication Systems and **Triple Seal™** Gearbox Protection.
- **Easy Connection:** The Woods Exclusive **Smartlift™** System holds your 37kg PTO driveline allowing you to easily connect and disconnect from the tractor.
- **Easy Maintenance: EZ-Change™** Blade System allows blade change in five steps with a ¾" spanner. No need to oxy or grind blade pins.
- **#1 in Cut Quality:** Enabled deep cutting decks, high-lift blades, structural framing and new features like Woods Exclusive **Level Lock™** Technology ensure a more level cut height across rugged terrain and even distribution of cut material.

Woods Advantages

- **Individual axle sprung wheels:** ensuring an even cut and smooth drive as wheels can absorb impact individually.
- Manufactured in the **United States of America**, assembled in **Australia**.
- 6.5mm thick and 330mm deep side skirt for **maximum handling of cut material**.
- **Full-strength baffled** underside frame ensures a smooth deck surface, minimizing cut material buildup and delivering a **robust, durable slasher**.

The BW15.72QRW Deck

Underside frame structure keeps the top deck clear to prevent water and debris buildup. Features include replaceable skid shoes, a 6.5 mm thick and 330 mm deep side skirt for optimal material handling, and 1-inch greasable wing pivot pins. The fully baffled deck uses 4.55 mm high-strength steel baffles welded to the frame, plus 3 mm welded baffles and deck rings on every deck for durability under extra heavy-duty conditions.

A SLASHER IS NOT JUST A SLASHER



Round deck rings on every deck add strength to the frame to handle extra heavy conditions.



Smartlift™ for easy connection to tractor.



Smooth top prevents accumulation of debris. Fully baffled 4.55mm high-strength steel frame. 6.5mm thick and 330mm deep side skirt for maximum handling of cut material.



Individual axle sprung wheels and walking tandem beams ensuring even cut and wheels individually absorb impact.



Exclusive Level-Lock™ Technology ensures a more level cut height across rugged terrain.



Walterscheid CAT 6 CV main, CAT 5 wing drivelines, 275hp splitter GB, 225hp spindle GB.



Heavy Duty Swivel towing eye reduces stress on equipment.

A SLASHER IS NOT JUST A SLASHER